

huddle hub
onehuddle hub
one+**USAGE SCENARIO****Virtual Huddle Room***Any space where people can meet, even if not equipped with display or camera*

•

•

Huddle Room*A small meeting room typically equipped with display and camera*

•

FEATURES**Device-to-device wireless presentation***Present your screen directly to the screen of all the other connected devices*

•

•

Multicam feed for UC clients*Turn your devices into a multi-camera, multi-screen video conferencing solution*

•

•

Layout selection*Customize the output layout generated by the multicam system*

•

•

On-screen presenter tool*Send your mouse cursor to viewers' screens*

•

•

Pin protected access*Secure your session with local, randomly generated pass code*

•

•

Browser based management*Configure one or many Huddle Hub units through a simple browser-based interface*

•

•

TV output*Plug in an optional display device to show your presentation on a large display (up to 1080p)*

•

Webcam input*Plug in an optional webcam to integrate its video stream into the device multicam output*

•

Connection via company network*Plug the Huddle Hub to your LAN and make it available everywhere in the company (Wi-Fi required)*

•

•

Connection via dedicated network*Take advantage of onboard Wi-Fi access point for a LAN independent connection*

•

Mixed network connection*Access Huddle Hub using both connections*

•

REQUIREMENTS

Presenter OS

Windows® 7 or higher, MacOS® 10.11 or higher, Android® 5 or higher

Viewer OS

Windows® 7 or higher, MacOS® 10.11 or higher
iOS® 10 or higher, Android® 5 or higherUC software clients
compatibilitySkype™, Skype for Business™, Hangouts™, WebEx™, Zoom™, Cisco Spark™,
GoToMeeting™, Cisco Spark, Slack™, etc.**SPECIFICATIONS**

Max number of connected devices

30

30

Max number of connected cameras in multicam feed

6

6

Wireless presentation resolution

Up to HD 1080p@30fps

Multicam feed resolution

Up to HD 720p@30fps

Wired network connection

Ethernet RJ-45 port, 1000 Mbit/s

Onboard dual-band access point

N/A

Wi-Fi IEEE 802.11 ac/a b g n 2.4/5
Ghz, 2 antennas

Wi-Fi authentication protocol

N/A

WPA2-PSK

Content encryption

AES 128

Webcam port

N/A

USB 2.0/3.0

TV port

N/A

HDMI

Power

External power adapter 12V DC

Dimensions (excluding antennas)

160 mm (6.3 in) x 132 mm (5.2 in) x 51 mm (2.0 in)

Weight

1030 g (2.27 lb)

1080 g (2.38 lb)

Case

Aluminum with fanless cooling

Temperature range

Operating: 0°C to +40°C (+32°F to +104°F)
Max: 35°C (95°F) at 3000m
Storage: -20°C to +60°C (-4°F to +140°F)

Mount

Table top or VESA mount (brackets included)

PCT Patent Application Pending.

*Last updated: 29 Jan 2018. Technical specifications are subject to change without prior notice. Please check www.hrt.website for the latest information. Copyright © HRT 2017
Huddle Hub, the HRT logo and other HRT marks are owned by HRT and may be registered. All other trademarks are the properties of their respective owners.*HRT Srl
Via Pio La Torre 13
41011 Campogalliano (MO)
ITALYHRT USA, Inc.
100 North Arlington Ave.
Suite 360
Reno, NV 89501 - USA